Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher International Products B.V.

Supplier's address: Product quality, Kingfisher International Products B.V. Rapenburgerstraat 175E 1011 VM Amsterdam The Netherlands

Model identifier: 3663602667780

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

rioudet parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
01	mption in on- 000 h), rounded est integer	6	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide in a narrow cone	500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode expressed in W	power (P _{on}),	5,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	79	Spectral power	See image		
dimensions	Width	45	distribution in the	in last page		
		1		Page 1/3		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	45	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,380		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	0	Survival factor	0,90		
the lumen main	tenance factor	0,93				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0		
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (P	'st LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)'-' : not applicable;

(b)'-' : not applicable;

