Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher International Products B.V.

Supplier's address: Product quality, Kingfisher International Products B.V. Rapenburgerstraat 175E 1011 VM Amsterdam The Netherlands

Model identifier: 3663602667872

Type of light source:

LED	Non-directional or directional:	NDLS
E14,		
220-240V~50Hz		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	E14, 220-240V~50Hz MLS No	directional: E14, 220-240V~50Hz MLS Connected light source (CLS): No Envelope: No

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	3	Energy efficiency class	G		
indicating if it re in a sphere (3)	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pexpressed in W	oower (P _{on}),	3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85		
Outer	Height	100	Spectral power	See image		
dimensions	Width	35	distribution in the	in last page		

without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	35	range 250 nm to 800 nm, at full-load				
Claim of equivalent pow	ver ^(a) -	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,458			
Parameters for LED and OLED light sources:						
R9 colour rendering inde	ex value 0	Survival factor	0,90			
the lumen maintenance	factor 0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (co	s ф1) 0,00	Colour consistency in McAdam ellipses	0			
Claims that an LEI source replaces a fluc light source without int ballast of a particular was	prescent regrated	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-': not applicable; (b)'-': not applicable;

