Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher International Products B.V.

Supplier's address: Product quality, Kingfisher International Products B.V. Rapenburgerstraat 175E 1011 VM Amsterdam The Netherlands

Model identifier: 3663602668527

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	E27,					
(or other electric interface)	220-240V~50Hz					
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

		: : Sauce para				
Parameter		Value	Parameter	Value		
General product parameters:						
0,	mption in on- 000 h), rounded est integer	13	Energy efficiency class	F		
indicating if it i in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	1 335 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode expressed in W	power (P _{on}),	13,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) essed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	113	Spectral power	See image		
dimensions	Width	80	distribution in the	in last page		
	L	1		Page 1/3		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	80	range 250 nm to 800 nm, at full-load				
Claim of equival	lent power ^(a)	-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,458			
Parameters for LED and OLED light sources:							
R9 colour rende	ring index value	0	Survival factor	0,90			
the lumen main	tenance factor	0,93					
Parameters for LED and OLED mains light sources:							
displacement fa	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0			
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (P	Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'-' : not applicable;

