## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher Int. Prod. B.V.

Supplier's address: Product quality, Kingfisher International Products B.V., Rapenburgerstraat

175E, 1011 VM Amsterdam, The Netherlands

Model identifier:	3663602670841
-------------------	---------------

т.,	nn	Λf	امزا	h+	50		co.
ıу	hΕ	UI	IIBI	IΙL	30	u	ce:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## Product parameters

Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P <sub>on</sub> ), expressed in W	8,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer Height	140	Spectral power	See image		
dimensions Width	95	distribution in the	in last page		

without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	95	range 250 nm to 800 nm, at full-load			
Claim of equivalent power		If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,381		
Parameters for LED and (	OLED light sources:				
R9 colour rendering index	k value 0	Survival factor	0,90		
the lumen maintenance f	actor 0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos	ф1) 0,00	Colour consistency in McAdam ellipses	0		
Claims that an LED source replaces a fluor light source without inte ballast of a particular wat	grated	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)'-': not applicable; (b)'-': not applicable;

