Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Kingfisher Int. Prod. B.V.

Supplier's address: Product quality, Kingfisher International Products B.V. Rapenburgerstraat 175E 1011 VM Amsterdam The Netherlands

Model identifier: 3663602770688

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Wire		
(or other electric interface)	connect,220-240V~ 50/60Hz		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	19	Energy efficiency class	F			
Useful luminous flux (ϕ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P _{on}), expressed in W	18,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			

Outer	Height	300	Spectral power	See image
dimensions	Width	300	distribution in the	in last page
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	35	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,380
Parameters for	LED and OLED lig	ht sources:	· · ·	
R9 colour rende	ring index value	0	Survival factor	0,90
the lumen main	tenance factor	0,94		
Parameters for	LED and OLED ma	ains light sources:		
displacement fa	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	lf yes then replacement claim (W)	-
Flicker metric (P	Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

