

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Cascade Holdings Ltd / INLIGHT

Supplier's address: Cascade Holdings Ltd, Gorse Street Gorse Mill, OL9 9RJ Oldham, UK

Model identifier: 46372-BHS BLK

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	LED integrated module		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------




General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		38	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 666 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000 or 6 000
On-mode power (P_{on}), expressed in W		38,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	180	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	560		
	Depth	560		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,439 0,402	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	20	Survival factor	1,00	
the lumen maintenance factor	0,90			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	


(a) '-': not applicable;

(b) '-': not applicable;



EPREL registration number: 2773631

Model placed on the Union market from 28/06/2026.



<https://eprel.ec.europa.eu/qr/2773631>

Supplier: Authorised Rep Compliance Limited (Authorised representative)

Website: www.authorisedrepcompliance.com

Customer care service:

Name: Cascade Holdings Ltd

Website: <https://www.cascadehl.com/>

Email: info@cascadehl.com

Phone: +44(0)1616286622

Address:

Gorse Street Gorse Mill
OL9 9RJ Oldham
United Kingdom