

PRODUCT SUMMARY

Valspar® Trade Contract Matt is a high opacity emulsion with strong covering power. Formulated specifically with the trade professional in mind, its spatter resistant formula is suitable for all interior walls and ceilings and can be applied direct to new plaster, straight from the bucket. Valspar® Trade - formulated for the perfect finish.

PRODUCT FEATURES & BENEFITS

- High opacity & coverage
- Direct to plaster
- Low spatter
- Tintable into Grey, Beige and Magnolia

RECOMMENDED USES/SUBSTRATES

- Plasterboard
- Dry wall
- Wallpaper
- New plaster

When using on new plaster, allow plaster to dry for at least 1 week before painting.

SPRAYER GUIDE

Application method: Brush, roller or sprayer

Sprayer	Airless SF23 Pro
Gun	Vector Pro
Tip Type	HEA Pro Tip
Tip Size	517
Dilution	0%
Spraying Pressure	1400 psi

*Derived from usage patterns of Wagner sprayers

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.
Protect from freezing.
Packaging: Case of 1

SURFACE PREPARATION

For indoor use only; avoid shower and high humidity areas. Remove grease, mould and dust completely for a clean & dry surface. Newly plastered surfaces should be fully dried/cured. For previously painted surfaces, wash, sand, and remove loose or flaky paint. Sand the surface before painting. Fill cracks, dents, or holes with a suitable filler. Use a suitable primer when painting difficult surfaces

APPLICATION

Stir paint thoroughly. Mix containers of the same colour for uniformity. Stop at a corner or natural break if running out of paint. Apply 2 coats using a suitable brush, roller, or sprayer. Avoid excessive rolling or brushing. Apply liberally, working from dry areas into the wet edge. Extra coats may be needed for dramatic colour changes. This paint does not need dilution, but if diluted use 10% water. When you dilute the paint you dilute the quality. Dries to the touch in approximately 1 hour. Wait 2-4 hours before applying the next coat. Allow 28 days to cure for ultimate durability.

STORAGE & DISPOSAL

CLEAN UP: Remove as much product from application equipment before cleaning. Do not wash paint down the drain when washing brushes and rollers. Clean painting tools with warm, soapy water. Wipe up spills immediately with a damp cloth.

STORAGE & DISPOSAL: Please dispose of unused paint responsibly. Check with your local authority to see if they provide facilities for the disposal of waste paint. If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses. Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EU limit for this product (Cat A/a): 30g/l (2010). This product contains a maximum VOC content <1 g/l. Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding."

PRODUCT SPECIFICATION

Product Type:

Acrylic water-based paint

Viscosity:

95-110 KU

Sheen:

Matt: <10 at 85°

VOC:

Trace

Volume Solid Content:

PBW - 15.87%

Coverage:

16m²/L

Touch dry:

1 hour

Recoat:

2 - 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C.

Storage temperature:

5 - 38°C – do not freeze

Certifications:

