

## PRODUCT SUMMARY

Valspar® Trade Primer and Undercoat features advanced water-based technology that is quick drying and low odour. Excellent opacity and covering power, as well as strong adhesion, ensures that interior walls & ceilings are prepared for a professional and durable finish.

## PRODUCT FEATURES & BENEFITS

- High opacity & covering power
- Strong adhesion
- Water-based

## RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings

## SHIPPING & PACKAGING

Freight classification: Paint or paint related material. Protect from freezing.

Packaging: Case of 1

## HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EU limit for this product (Cat A/g): 30g/l (2010). This product contains a maximum VOC content <1 g/l.

Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding.

Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

## SURFACE PREPARATION

Read health and safety information below before painting.

- For interior use
- Do not apply in damp or humid conditions
- Surface must be clean, dry and free of dust, grease and mould
- Glossy surfaces should be deglossed before painting
- Remove old, loose or flaky paint and repair all damaged areas before painting

## APPLICATION

- Stir well before use to ensure paint is thoroughly mixed
- Apply using a suitable brush, roller or sprayer.
- If doing a dramatic colour change, you may require additional coats
- Do not thin this product
- Dries to the touch in approximately an hour. Allow 2-4 hours between coats

## STORAGE & DISPOSAL

### CLEAN UP

- Remove as much product from application equipment before cleaning
- Do not wash paint down the drain when washing brushes and rollers
- Clean painting tools with warm, soapy water
- Wipe up spills immediately with a damp cloth

### STORAGE & DISPOSAL

- Please dispose of unused paint responsibly
- Check with your local authority to see if they provide facilities for the disposal of waste paint
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses
- Protect from frost

## PRODUCT SPECIFICATION

### Product Type:

Acrylic water-based paint

### Viscosity:

PBW: 105-120 KU  
Grey: 100-115 KU

### Sheen:

0-10 at 85°

### VOC:

Trace

### Solid content of base:

PBW: 26-27%  
Grey: 26-27%

### Coverage:

10m<sup>2</sup>/L

### Touch dry:

1 hour

### Recoat:

2 - 4 hours

### Application temperature:

Apply in dry conditions above a minimum temperature of 10°C.

### Storage temperature:

5 - 38°C – do not freeze

### Certifications:

