

PRODUCT SUMMARY

Valspar® Classic Walls & Ceilings is a versatile emulsion with great coverage in true HD colour. With a water-based formula that's quick drying, low spatter, and wipeable, it is easy to use and keep clean – even in a matt finish. Valspar Classic endures the scuffs and knocks of daily living without compromising your colour or finish, so the walls and ceilings in your home look great for longer.

Any colour, no compromise, with Valspar.

PRODUCT FEATURES & BENEFITS

- Durable and washable
- Stain resistant
- Quick drying

RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings

APPLICATION

- Stir paint thoroughly.
- Mix containers of the same colour for uniformity.
- Stop at a corner or natural break if running out of paint.
- Apply 2 coats using a suitable brush, roller, or sprayer.
- Avoid excessive rolling or brushing.
- Apply liberally, working from dry areas into the wet edge.
- Extra coats may be needed for dramatic colour changes.
- When you dilute the paint, you dilute the quality.
- Dries to touch in approximately 1 hour.
- Wait 2-4 hours before applying the next coat.
- Allow 28 days to cure for ultimate durability.

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.

Protect from freezing.

Packaging: Case of 1

SHERWIN-WILLIAMS.

SURFACE PREPARATION

Read health and safety information before painting.

- For indoor use only; avoid showers and high humidity areas.
- Do not apply in damp or humid conditions.
- Remove grease, mould and dust completely for a clean & dry surface
- Sand the surface before painting.
- For previously painted surfaces, wash, sand thoroughly, and remove loose or flaky paint
- Fill cracks, dents, or holes with a suitable filler.
- Use a suitable primer when making bold colour changes or when painting difficult surfaces

STORAGE & DISPOSAL

- Remove as much product from application equipment before cleaning.
- Do not wash paint down the drain when washing brushes and rollers.
- Clean painting tools with warm, soapy water.
- Wipe up spills immediately with a damp cloth
- Please dispose of unused paint responsibly.
- Check with your local authority to see if they provide facilities for the disposal of waste paint.
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses.
- Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, then dispose with household rubbish.
- Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one, 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Avoid inhalation of dust. Wear a face mask if dry sanding. VOC content: EU limit for this product (Category A/a): 30 g/l (2010). This product contains a maximum VOC content of 1 g/l.

Please contact Valspar Customer Service on for the safety datasheet, available on request.

PRODUCT SPECIFICATION

Product type:

Acrylic water based

Viscosity:

100 – 120 KU

Sheen:

Matt	0 – 10 (85°)
------	--------------

Silk	20 – 35 (60°)
------	---------------

VOC (g/l):

Trace

Volume solids (before colourant added):

Base A	30% – 36%
--------	-----------

Base B	27% – 29%
--------	-----------

Base C	22% - 31%
--------	-----------

Coverage:

10m²/l

Touch dry:

1 hour

Recoat:

2 – 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C

Storage temperature:

Avoid extreme temperatures – do not freeze

Time to cure:

28 days

Test methods:

Our R&D laboratory performs tests following the ISO test methods.



For help & advice visit valsparpaint.co.uk or call **0344 736 9174** (UK) / **35319075488** (ROI)

Sherwin-Williams UK Limited, Avenue One, Station Lane, Witney, Oxfordshire, OX28 4XR, UK

Sherwin-Williams (Ireland) Ltd, Registered in Ireland 088980, Unit 53, Robinhood Industrial Estate, Dublin 22, D22 PW99

Valspar is a registered trademark of the Sherwin-Williams Company © 2024