

MULTI-SURFACE DEAD FLAT MATT

PRODUCT SUMMARY

V&CO premium paint offers an exceptional Dead-Flat Matt finish with rich depth of colour and superior durability. The advanced formula is hardwearing and scrubbable ensuring your Walls, Ceilings Wood and Radiators remain immaculate.

PRODUCT FEATURES & BENEFITS

- Exceptional Dead-Flat Matt finish
- Superior durability
- Ultimate dirt and stain resistant
- Hardwearing and scrubbable
- Highly pigmented
- Maximum coverage and hide
- Water based and low splatter

RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings
- Wood
- Radiators

APPLICATION

Stir contents to ensure paint is thoroughly mixed. Purchase enough paint to complete the job. When purchasing more than one container of the same colour, intermix containers to ensure colour uniformity. If you feel that you may run out of paint, stop at a corner or a natural break. Apply 1-2 coats using a suitable brush, roller or sprayer. Apply liberally, working from dry areas into the paint's wet edge and finish with gentle, vertical strokes. Avoid excessive rolling or brushing. Extra coats may be required when making dramatic colour changes. Do not thin this product. Dries to the touch in approximately 1 hour under normal conditions. Allow 2-4 hours between coats.

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.
Protect from freezing.
Packaging: Case of 1

SHERWIN-WILLIAMS.

SURFACE PREPARATION

For indoor use only. Do not apply in damp or humid conditions.

Apply when the temperature of the surface being painted is above 10°C. Glossy surfaces should be deglossed before painting. Repair all damaged areas before painting. Remove old, loose or flaky paint. New, fresh plaster must be sealed with Valspar® Interior Primer & Undercoat prior to painting. Other bare, absorbent surfaces must be sealed with primer or a first coat of this product prior to applying the finishing coat.

STORAGE & DISPOSAL

Dispose of unused paint responsibly. Check with your local authority to see if they provide facilities for the disposal of paint. Remove as much paint as possible from rollers and brushes before washing. Do not wash the paint down the drain when cleaning. Don't empty leftover paint into drains or watercourses. Pour it into a box with shredded paper or cat litter, allow it to solidify away from children or pets, then dispose with household rubbish. Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. VOC content: EU limit for this product (Category A/a): 30 g/l (2010). This product contains a maximum VOC content of <1 g/l. Water-based paint. When applying, it is advisable to wear eye protection. Avoid inhalation of dust. Wear a face mask if dry sanding.

Please contact Valspar Customer Service for the safety datasheet, available on request.

PRODUCT SPECIFICATION

Product type:

Acrylic water-based paint

Viscosity:

100 – 120 KU

Sheen:

0 - 5 (85°)

VOC (G/L):

Trace

Volume solids (before colourant added):

Base A 41% - 42%

Base B 36% - 37%

Base C 31% - 32%

Coverage:

12m²/l

Touch dry:

1 hour

Recoat:

2 – 4 hours

Application temperature:

Apply in dry conditions above minimum temperature of 10°C

Storage temperature:

Avoid extreme temperatures – do not freeze

Time to cure:

28 days

Test methods:

Our R&D laboratory performs tests following the ISO test methods.

