

PRODUCT SUMMARY

Valspar Simplicity Walls & Ceilings is an easy-to-use emulsion. This low splatter paint creates a smooth finish, giving great, even coverage. It's also lightweight meaning you can achieve your new look with minimal effort, whilst being wipeable and easy to maintain. Valspar Simplicity's water-based formula means it's both quick drying and easy to clean up, so you can spend more time enjoying your transformation.

PRODUCT FEATURES & BENEFITS

- Wipeable
- Quick drying

RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings

APPLICATION

- Stir paint thoroughly.
- Mix containers of the same colour for uniformity.
- Stop at a corner or natural break if running out of paint.
- Apply 2 coats using a suitable brush, roller, or sprayer.
- Avoid excessive rolling or brushing.
- Apply liberally, working from dry areas into the wet edge.
- Extra coats may be needed for dramatic colour changes.
- When you dilute the paint, you dilute the quality.
- Dries to touch in approximately 1 hour.
- Wait 2-4 hours before applying the next coat.
- Allow 28 days to cure for ultimate durability.

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.
Protect from freezing.
Packaging: Case of 1

SURFACE PREPARATION

- Read health and safety information before painting.
- For indoor use only; avoid showers and high humidity areas.
- Do not apply in damp or humid conditions.
- Remove grease, mould and dust completely for a clean & dry surface
- Sand the surface before painting.
- For previously painted surfaces, wash, sand thoroughly, and remove loose or flaky paint
- Fill cracks, dents, or holes with a suitable filler.
- Use a suitable primer when making bold colour changes or when painting difficult surfaces

STORAGE & DISPOSAL

- Remove as much product from application equipment before cleaning.
- Do not wash paint down the drain when washing brushes and rollers.
- Clean painting tools with warm, soapy water.
- Wipe up spills immediately with a damp cloth.
- For ultimate durability, allow 28 days to cure.
- Please dispose of unused paint responsibly.
- Check with your local authority to see if they provide facilities for the disposal of waste paint.
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses.
- Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, then dispose with household rubbish.
- Protect from frost

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one, 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Avoid inhalation of dust. Wear a face mask if dry sanding. VOC content: EU limit for this product (Category A/a): 30 g/l (2010). This product contains a maximum VOC content of 1 g/l.

Please contact Valspar Customer Service for the safety datasheet, available on request.

PRODUCT SPECIFICATION

Product type:	Acrylic water-based paint
Viscosity:	100 – 115 KU
Sheen:	0 - 10 (85°)
VOC (g/l):	Trace
Volume solids (before colourant added):	21% - 22%
Coverage:	10m ² /L
Touch dry:	1 hour
Recoat:	2 – 4 hours
Application temperature:	Apply in dry conditions above a minimum temperature of 10°C
Storage temperature:	Avoid extreme temperatures – do not freeze
Time to cure:	28 days
Test methods:	Our R&D laboratory performs tests following the ISO test methods.



SHERWIN-WILLIAMS.



For help & advice visit valsparpaint.co.uk or call **0344 736 9174** (UK) / **35319075488** (ROI)
Sherwin-Williams UK Limited, Avenue One, Station Lane, Witney, Oxfordshire, OX28 4XR, UK
Sherwin-Williams (Ireland) Ltd, Registered in Ireland 088980, Unit 53, Robinhood Industrial Estate, Dublin 22, D22 PW99
Valspar is a registered trademark of the Sherwin-Williams Company © 2024