

PRODUCT SUMMARY

Valspar® Premium Masonry features a microporous film, making it breathable and tough for long-term protection. It's showerproof in just 30 minutes and can be applied to damp surfaces. Valspar® Premium Masonry has built-in self-cleaning technology and is UV resistant so it won't crack, blister or peel, ensuring your surface is protected against harsh weather conditions. Any colour, no compromise, with Valspar.

PRODUCT FEATURES & BENEFITS

- UV and crack resistant
- Resistant to mould growth on the paint surface
- Self-cleaning
- Excellent coverage
- Microporous and breathable
- 20-year all weather protection

RECOMMENDED USES/SUBSTRATES

- Prime with Valspar Trade Masonry Stabilizing Solution
- Brick
- Concrete
- Cement
- Stone
- Painted surfaces
- Pebbledash
- Stucco
- Roughcast rendering

APPLICATION

- Stir contents to ensure paint is thoroughly mixed.
- When purchasing more than one container of the same colour, intermix containers to ensure colour uniformity.
- If you feel that you may run out of paint, stop at a corner or a natural break.
- Apply 2 coats using a suitable brush, roller or sprayer.
- Avoid excessive rolling or brushing.
- Apply liberally, working from dry areas into the paint's wet edge.
- Extra coats may be required when making dramatic colour changes.
- When you dilute the formula, you dilute the quality.
- Dries to the touch in about one hour under normal conditions.
- Allow 2-4 hours for next coats.

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.
Protect from freezing.
Packaging: Case of 1

SHERWIN-WILLIAMS.

SURFACE PREPARATION

- Read health and safety information before painting
- Do not paint in damp or humid conditions
- Ensure the surface temperature is above 10°C
- Remove grease, algae and dust completely for a clean & dry surface
- For previously painted surfaces, wash, sand, and remove loose or flaky paint
- Wait 4-6 weeks before painting new surfaces
- Repair any damaged areas
- Sand surfaces before painting
- Prime with Valspar Trade Masonry Stabilizing Solution

STORAGE & DISPOSAL

- Remove as much product from application equipment before cleaning.
- Do not wash paint down the drain when washing brushes and rollers.
- Clean painting tools with warm, soapy water.
- Wipe up spills immediately with a damp cloth.
- Please dispose of unused paint responsibly.
- Check with your local authority to see if they provide facilities for the disposal of waste paint.
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses.
- Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, then dispose with household rubbish.
- Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product for the protection of the dry paint film from mould growth: IPBC & Terbutryn. Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Avoid inhalation of dust. Wear a face mask if dry sanding. VOC content: EU limit for this product (Category A/c): 40 g/l (2010). This product contains a maximum VOC content of 1 g/l.

Please contact Valspar Customer Service for the safety datasheet, available on request.

PRODUCT SPECIFICATION

Product type:

Acrylic water-based paint

Viscosity:

105 – 130 KU

Sheen:

0 – 10 (85°)

VOC (g/l):

Trace

Volume solid (before colourant added):

Base 1 38% - 39%

Base 2 37% - 28%

Base 3 35% - 36%

Coverage

10m²/L

Touch dry:

1 hour

Recoat:

2 – 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C

Storage temperature:

Avoid extreme temperatures – do not freeze

Time to cure:

28 days

Test methods:

Our R&D laboratory performs tests following the ISO test methods.



For help & advice visit **valsparpaint.co.uk** or call **0344 736 9174 (UK) / 35319075488 (ROI)**
Sherwin-Williams UK Limited, Avenue One, Station Lane, Witney, Oxfordshire, OX28 4XR, UK
Sherwin-Williams (Ireland) Ltd, Registered in Ireland 088980, Unit 53, Robinhood Industrial Estate, Dublin 22, D22 PW99
Valspar is a registered trademark of the Sherwin-Williams Company © 2024