

PRODUCT SUMMARY

Valspar® Trade Vinyl Matt is a professional, high opacity emulsion with strong covering power. It's washable, providing long-term performance and colours that stay true for years, with a matt finish that is perfect for walls and ceilings in critical lighting. This water-based formula is quick drying and low spatter, and can be applied in temperatures as low as 2°C. Valspar® Trade - formulated for the perfect finish.

PRODUCT FEATURES & BENEFITS

- High opacity & covering power
- Ideal for walls and ceilings in critical lighting
- Hides imperfections

RECOMMENDED USES/SUBSTRATES

- Walls
- Ceilings

SPRAYER GUIDE

Application method: Brush, roller or sprayer

Sprayer	Airless SF 23 Pro
Gun	Vector Pro
Tip Type	HEA ProTip
Tip Size	517
Dilution	0%
Spraying Pressure	1400 psi

*Derived from usage patterns of Wagner sprayers

SHIPPING & PACKAGING

Freight classification: Paint or paint related material.

Protect from freezing.
Packaging: Case of 1

SURFACE PREPARATION

Stir paint thoroughly. Mix containers of the same colour for uniformity. Stop at a corner or natural break if running out of paint. Apply 2 coats using a suitable brush, roller, or sprayer. Avoid excessive rolling or brushing. Apply liberally, working from dry areas into the wet edge. Extra coats may be needed for dramatic colour changes. To use as a mist coat, dilute with 20% water. When you dilute the paint, you dilute the quality. Dries to the touch in approximately 1 hour. Wait 2-4 hours before applying the next coat. Allow 28 days to cure for ultimate durability.

APPLICATION

For indoor use only; avoid shower and high humidity areas. You can apply this paint in temperatures as low as 2°C. Remove grease, mould and dust completely for a clean & dry surface. New plaster and other bare, absorbent surfaces must be sealed. For previously painted surfaces, wash, sand, and remove loose or flaky paint. Sand the surface before painting. Fill cracks, dents, or holes with a suitable filler. Use a suitable primer when making bold colour changes or when painting difficult surfaces

STORAGE & DISPOSAL

CLEAN UP: Remove as much product from application equipment before cleaning. Do not wash paint down the drain when washing brushes and rollers. Clean painting tools with warm, soapy water. Wipe up spills immediately with a damp cloth.

STORAGE & DISPOSAL: Please dispose of unused paint responsibly. Check with your local authority to see if they provide facilities for the disposal of waste paint. If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses. Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, then dispose with household rubbish. Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EU limit for this product (Cat A/a): 30g/l (2010). This product contains a maximum VOC content of 5 g/l. Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding.

PRODUCT SPECIFICATION

Product Type:

Acrylic water-based paint

Viscosity:

125-140 KU

Sheen:

Matt: <0-5 at 85°

VOC:

Low

Volume Solid (before colourant):

Base A – 27.21%
Base B – 27.38%
Base C – 22.04%
PBW – 29.68%

Coverage:

16m²/L

Touch dry:

1 hour

Recoat:

2 - 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 2°C.

Storage temperature:

5 - 38°C – do not freeze

Certifications:

Eurofins Indoor Air Quality Gold

