

PRODUCT SUMMARY

Valspar® Trade Knot Block Wood Primer and Undercoat is a dual-purpose paint that stops bleed-through from wood knots, prevents cracking and peeling, and seals knots and sap streaks. Our advanced water-based technology promises high opacity and covering power, on both softwoods and hardwoods. Quick drying, low odour, and strong adhesion of the top coat promises a high-quality finish. Valspar® Trade - formulated for the perfect finish.

PRODUCT FEATURES & BENEFITS

- Seals knots and sap streaks
- Strong adhesion
- High opacity & covering power

RECOMMENDED USES/SUBSTRATES

- Hardboard
- Softwood
- Hardwood
- Old paint

SHIPPING & PACKAGING

Freight classification: Paint or paint related material. Protect from freezing.

Packaging: Case of 1

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EU limit for this product (Cat A/i): 140g/l (2010). This product contains a maximum VOC content of 50 g/l.

Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding.

Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

SURFACE PREPARATION

Read health and safety information below before painting.

- Do not apply in damp or humid conditions
- Apply when the temperature of the surface being painted is above 10°C
- New or bare metal should be sanded prior to painting
- The surface must be clean, dry and free of dust, grease and mould
- Remove any loose rust
- Glossy surfaces should be deglossed before painting
- Any damaged or rotten timber should be repaired prior to painting

APPLICATION

- Stir well before use to ensure paint is thoroughly mixed
- Apply using a suitable brush, roller or sprayer
- Dries to the touch in about 30 minutes
- Allow 2-4 hours between coats
- Do not thin this product. When you dilute the paint, you dilute the quality

STORAGE & DISPOSAL

CLEAN UP

- Remove as much product from application equipment before cleaning
- Do not wash paint down the drain when washing brushes and rollers
- Clean painting tools with warm, soapy water
- Wipe up spills immediately with a damp cloth

STORAGE & DISPOSAL

- Please dispose of unused paint responsibly
- Check with your local authority to see if they provide facilities for the disposal of waste paint
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses
- Protect from frost

PRODUCT SPECIFICATION

Product Type:

Acrylic water-based paint

Viscosity:

75-85 KU

Sheen:

0-25 at 85°

VOC:

Low

Solid content of base:

47-48%

Coverage:

10m²/L

Touch dry:

1 hour

Recoat:

2 - 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C.

Storage temperature:

5 - 38°C – do not freeze

Certifications:

