

PRODUCT SUMMARY

Valspar® Trade Metal Primer is a high-performance metal primer that can be applied directly to rust. Our advanced water-based technology is quick drying and low odour. The primer provides strong adhesion of the topcoat, preventing cracking and peeling, alongside high opacity and covering power for a high-quality finish. Valspar® Trade - formulated for the perfect finish.

PRODUCT FEATURES & BENEFITS

- Direct to rust
- High opacity & covering power
- Strong adhesion
- Low odour
- Water-based

RECOMMENDED USES/SUBSTRATES

- Bare metal
- Rusted steel
- Cast iron
- Galvanised steel
- Aluminium
- Stainless steel

SHIPPING & PACKAGING

Freight classification: Paint or paint related material. Protect from freezing.

Packaging: Case of 1

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one and 3-aminopropyltriethoxysilane. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EU limit for this product (Cat A/i): 140g/l (2010). This product contains a maximum VOC content of 45 g/l. Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

SURFACE PREPARATION

Read health and safety information below before painting.

- Do not apply in damp or humid conditions
- Apply when the temperature of the surface being painted is above 10°C
- New or bare metal should be sanded prior to painting
- The surface must be clean, dry and free of dust, grease and mould
- Remove any loose rust
- Glossy surfaces should be deglossed before painting

APPLICATION

- Stir well before use to ensure paint is thoroughly mixed
- Apply using a suitable brush, roller or sprayer
- Dries to the touch in about 30 minutes
- Allow 2-4 hours between coats
- Do not thin this product. When you dilute the paint, you dilute the quality

STORAGE & DISPOSAL

CLEAN UP

- Remove as much product from application equipment before cleaning
- Do not wash paint down the drain when washing brushes and rollers
- Clean painting tools with warm, soapy water
- Wipe up spills immediately with a damp cloth

STORAGE & DISPOSAL

- Please dispose of unused paint responsibly
- Check with your local authority to see if they provide facilities for the disposal of waste paint
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses
- Protect from frost

PRODUCT SPECIFICATION

Product Type:

Acrylic water-based paint

Viscosity:

80-100 KU

Sheen:

0-10 at 85°

VOC:

Low

Solid content of base:

37-41%

Coverage:

10m²/L

Touch dry:

1 hour

Recoat:

2 - 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C.

Storage temperature:

5 - 38°C – do not freeze

Certifications:



© BRITISH COATINGS FEDERATION LTD ALL RIGHTS RESERVED

