

PRODUCT SUMMARY

Valspar® Trade Masonry Smooth with SeasonFlex technology is a high-quality, microporous and hydrophobic paint for exterior walls. Formulated for the professional, it can be applied in all seasons in temperatures above 2°C. The microporous film helps evacuate wall humidity. It's showerproof 30 minutes after application, and our 20 year all weather protection promises UV resistance for improved longevity. Valspar® Trade - formulated for the perfect finish.

PRODUCT FEATURES & BENEFITS

- Showerproof in 30 minutes
- Microporous and hydrophobic
- 20 Year All-Weather Protection

RECOMMENDED USES/SUBSTRATES

- Brick
- Concrete
- Cement
- Stone
- Stucco
- Pebbledash
- Roughcast render

SPRAYER GUIDE

Application method: Brush, roller or sprayer

Sprayer	Airless SF 23 Pro
Gun	Vector Pro
Tip Type	Trade Tip 3
Tip Size	421
Dilution	0%
Spraying Pressure	2000-2200 psi

*Derived from usage patterns of Wagner sprayers

SHIPPING & PACKAGING

Freight classification: Paint or paint related material. Protect from freezing.

Packaging: Case of 1

SURFACE PREPARATION

Read health and safety information below before painting. Do not paint in damp or humid conditions. This product can be applied in temperatures as low as 2°C. Remove grease, algae and dust completely for a clean & dry surface. For previously painted surfaces, wash, sand, and remove loose or flaky paint. Wait 4-6 weeks before painting new surfaces. Repair any damaged areas. Sand surfaces before painting. Loose, chalky surfaces should be primed with Valspar Trade Masonry Stabilizing Solution. Rust staining or rust deposits should be primed with using Valspar Trade Metal Primer

APPLICATION

Allow 4 hours between coats depending on weather conditions. In low temperatures product dries slower and achieved water resistance later. Stir paint thoroughly. Mix containers of the same colour for uniformity. Stop painting at a corner or natural break if running out of paint. Apply 2 coats using a suitable brush, roller, or sprayer. Avoid excessive rolling or brushing. Apply liberally, working from dry areas into wet edges. Extra coats may be needed for dramatic colour changes. Do not thin this product. When you dilute the paint, you dilute the quality. Dries to the touch in approximately 1 hour. Wait 2-4 hours before applying the next coat. Allow 28 days to cure for ultimate durability.

STORAGE & DISPOSAL

CLEAN UP: Remove as much product from application equipment before cleaning. Do not wash paint down the drain when washing brushes and rollers. Clean painting tools with warm, soapy water. Wipe up spills immediately with a damp cloth.

STORAGE & DISPOSAL: Please dispose of unused paint responsibly. Check with your local authority to see if they provide facilities for the disposal of waste paint. If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses. Protect from frost.

HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EU limit for this product (Cat A/c): 40g/l (2010). This product contains a maximum VOC content of 7 g/l. Water-based paint. Ensure good ventilation during drying and application. When applying it is advisable to wear eye protection. Avoid inhalation of dust, wear a face mask when dry sanding.

PRODUCT SPECIFICATION

Product Type:

Acrylic water-based paint

Viscosity:

110 – 130 KU

Sheen:

Smooth: 0-10 at 85°

VOC:

Low

Solid content of base (before colourant):

Base A – 38-39%
Base B – 37-38%
Base C – 35-36%
PBW – 38-39%

Coverage:

14m²/L

Touch dry:

30 mins

Recoat:

2 - 4 hours

Application temperature:

10 - 32°C

Storage temperature:

5 - 38°C – do not freeze

Testing & Certifications:

SD Value: 0.118 – 0.140

