

## PRODUCT SUMMARY

Valspar® Premium Exterior Floor is a tough and weatherproof paint especially formulated for exterior use. Its UV, crack, and mould-resistant formula provides excellent coverage paired with great flow and levelling, ensuring a perfectly smooth finish in half the time. Suitable for a range of flooring, from tarmac to bricks and concrete. With long-term performance you can rely on, your colour will stay true for years to come. Any colour, no compromise, with Valspar.

## PRODUCT FEATURES & BENEFITS

- UV and crack resistant
- Resistant to mould growth on the paint surface in damp areas
- Long lasting colours
- Excellent coverage
- Quick drying

## RECOMMENDED USES/SUBSTRATES

- Tarmac
- Paving slabs
- Paving stones
- Concrete
- Bricks
- Wood

## APPLICATION

- Stir paint thoroughly.
- Mix containers of the same colour for uniformity.
- Stop at a corner or natural break if running out of paint.
- Apply 2 coats using a suitable brush, roller, or sprayer.
- Avoid excessive rolling or brushing.
- Apply liberally, working from dry to wet edges.
- Extra coats may be needed for dramatic colour changes.
- When you dilute the paint, you dilute the quality.
- Dries to the touch in approximately 1 hour.
- Wait 2-4 hours before applying the next coat.
- Wait 72 hours before parking cars or motorcycles on the painted floor.
- Allow 28 days to cure for ultimate durability.

## SHIPPING & PACKAGING

Freight classification: Paint or paint related material.  
Protect from freezing.  
Packaging: Case of 1

SHERWIN-WILLIAMS.

## SURFACE PREPARATION

- Read health and safety information before painting
- Do not paint in damp or humid conditions
- Ensure the surface temperature is above 10°C
- Remove grease, algae and dust completely from the surface
- For previously painted surfaces, wash, sand, and remove loose or flaky paint
- Ensure concrete floors are clean, dry, and not pre-finished to avoid cracks and blisters
- Wait 4-6 weeks before painting new surfaces and 90 days for new concrete floors
- Repair any damaged areas
- Sand surfaces before painting.
- Do not use on powdery surfaces
- Prime with Valspar Trade Masonry Stabilizing Solution

## STORAGE & DISPOSAL

- Remove as much product from application equipment before cleaning.
- Do not wash paint down the drain when washing brushes and rollers.
- Clean painting tools with warm, soapy water.
- Wipe up spills immediately with a damp cloth.
- Please dispose of unused paint responsibly.
- Check with your local authority to see if they provide facilities for the disposal of waste paint.
- If you have leftover paint that cannot be re-used or stored, do not empty into drains or watercourses.
- Pour the leftover paint into a box with shredded paper or cat litter, allow it to solidify in a well-ventilated area away from children or pets, then dispose with household rubbish.
- Protect from frost.

## HEALTH & SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product for the protection of the dry paint film from mould growth: IPBC & Terbutryn. Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Avoid inhalation of dust. Wear a face mask if dry sanding. VOC content: EU limit for this product (Category A/i): 140 g/l (2010). This product contains a maximum VOC content of 15 g/l.

Please contact Valspar Customer Service for the safety datasheet, available on request.

## PRODUCT SPECIFICATION

Product type:

Acrylic water-based paint

Viscosity:

75 – 100 KU

Sheen:

10 – 20 (60°)

VOC:

Low

Volume solids (before colourant added):

Base 1 25% - 26%

Base 2 27% - 28%

Base 3 29% - 30%

Coverage:

10m<sup>2</sup>/L

Touch dry:

1 hour

Recoat:

2 – 4 hours

Application temperature:

Apply in dry conditions above a minimum temperature of 10°C

Storage temperature:

Avoid extreme temperatures – do not freeze

Time to cure:

28 days

Test methods:

Our R&D laboratory performs tests following the ISO test methods.

