

SBS TORCH-ON CAP SHEET & UNDERLAY

Torch-on membranes are rolled and applied hot, using a propane torch to heat the underside, which releases the molten bitumen to provide adhesion to a flat roof

- Cap Sheet and Underlay for a 2-part system
- SBS modified bituminous membranes
- Polyester reinforced for better tear resistance
- Black Cap Sheet, Sand finish Underlay
- Less heat required to melt SBS bitumen than APP and more flexible in a wider temperature range
- 12 Year Life Expectancy
- Suitable for habitable buildings



CE	13 0809-CPR-21000631 EN 13707:2004+A2:2009
	DoP available at https://rooftrade.co.uk Flexible reinforced bitumen sheets for roof waterproofing
Radmat Building Products Limited Holland House, Valley Way, Rockingham Road, Market Harborough, Leicestershire, LE16 7PS, UK	

UK CA
UK 0836-CPR-13/F049 BSEN: 13707:2013



Where refurbishment is required to existing flat roofs it is advisable to check with Local Authority Building Control (LABC) before commencing the work.

Specifiers should check the National Federation of Roofing Contractors (NRF) "Safe2Torch" guidance at: - <https://www.nfrc.co.uk/docs/default-source/health-and-safety-guidance-publications/safe2torch-guidance.pdf>

Remember that all construction specification and detailing must conform with UK Building Regulations.