

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Kingfisher Int. Prod. B.V.

**Supplier's address:** Marcus Muktarsing, Hammerweg 44, 7731 AK Ommen, Netherlands 7731, Netherlands AK Ommen, , NL

**Model identifier:** 5063022074904

## Type of light source:

|   |                   |                                 |      |
|---|-------------------|---------------------------------|------|
| Lighting technology used:                           | LED               | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | G13,220-240V~50Hz |                                 |      |
| Mains or non-mains:                                 | MLS               | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No                | Envelope:                       | -    |
| High luminance light source:                        | No                |                                 |      |
| Anti-glare shield:                                  | No                | Dimmable:                       | No   |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|   |        |                        |  |                        |
|---|--------|------------------------|--|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer   |        | 24                     | Energy efficiency class  | D                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |        | 3 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W   |        | 24,0                   | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal  | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal  |        | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                     |
| Outer dimensions without separate control gear, light-  | Height | 28                     | Spectral power distribution in the range 250 nm to 800 nm, at full-load  | See image in last page |
|   | Width  | 28                     |  |                        |
|   | Depth  | 1 778                  |  |                        |

|   |      |                                       |                |  |
|---|------|---------------------------------------|----------------|--|
| ing control parts and non-lighting control parts, if any (millimetre)   |      |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)          | -              |  |
|   |      | Chromaticity coordinates (x and y)    | 0,381<br>0,379 |  |
| <b>Parameters for LED and OLED light sources:</b>   |      |                                       |                |  |
| R9 colour rendering index value   | 0    | Survival factor                       | 0,90           |  |
| the lumen maintenance factor  | 0,96 |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>   |      |                                       |                |  |
| displacement factor (cos $\phi_1$ )   | 0,70 | Colour consistency in McAdam ellipses | 6              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)   | 1,0  | Stroboscopic effect metric (SVM)      | 0,9            |  |

(a) '-': not applicable;

(b) '-': not applicable;

