






EN Socker tester UK

EN

Safety Notes

- The unit is only intended to be used for short periods, typically less than 5 minutes, and must not be left plugged in for extended periods. Vent slots should not be covered or obstructed.
- The unit is intended for use in the vertical orientation only. The unit must always be checked for any sign of damage do not use. Visual signs of damage include checking the case exterior, pins and label. If any are damaged DO NOT USE.
- To verify the tester is working correctly. Always first plug it into a known good socket prior to use.
- If the unit has suffered a mechanical shock such as a drop, have it checked out first.
- The product has no user serviceable parts.
- The product will not detect reverse earth neutral.
- The Socket Polarity Tester is intended as a first level fault indication tool and only checks for correct polarity.
- If RED is indicated by the LED's, unplug the unit immediately and check the installation wiring.
- The Socket Polarity Tester is designed to test sockets in one easy step.
- The test procedure is very simple. Plug the unit into a mains socket and the Socket Polarity Tester will light up GREEN, GREEN, OFF to indicate correct wiring. Any other combination indicates a fault. Please refer to the table opposite for a list of fault indications.

Symbols

	This symbol adjacent to another symbol, terminal or operating device indicates that the operator must refer to an explanation in the Operating Instructions to avoid personal injury or damage to the meter.
WARNING	This WARNING symbol indicates a potentially hazardous situation, which if not avoided, could result in death or serious injury.
CAUTION	This CAUTION symbol indicates a potentially hazardous situation, which if not avoided, may result damage to the product.
	This symbol advises the user that the terminal(s) so marked must not be connected to a circuit point at which the voltage with respect to earth ground exceeds (in this case) 1000 V AC or 1500 V DC.
	This symbol adjacent to one or more terminals identifies them as being associated with ranges that may, in normal use, be subjected to particularly hazardous voltages. For maximum safety, the meter and its test leads should not be handled when these terminals are energized.
UK CA	Conformity with all the applicable requirements for products sold within Great Britain.
CE	Conformity with all relevant EC Directive requirements.
	Waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your Local Authority or local store for recycling advice.
	Alternating current (AC)

Technical Specifications

Operation range	230 V AC
Frequency Range	50 Hz
Operating Temperature	0 to 50 °C (32 to 122 °F)
Storage Temperature	-10 to 60 °C (14 to 140 °F)
Humidity	80% max.
Altitude	2000 meters
Pollution Degree	2
Safety Compliance	CAT III 300 V
Wet location	Not intended
For indoor use only.	

Guarantee

We take special care to select high quality materials and use manufacturing techniques that allow us to create products incorporating design and durability. This product has a manufacturer's guarantee of 2 years against manufacturing defects, from the date of purchase (if bought in store) or date of delivery (if bought online), at no additional cost for normal (non-professional or commercial) household use.

To make a claim under this guarantee, you must present your proof of purchase (such as a sales receipt, purchase invoice or other evidence admissible under applicable law), please keep your proof of purchase in a safe place. For this guarantee to apply, the product you purchased must be new, it will not apply to second hand or display products. Unless stated otherwise by applicable law, any replacement product issued under this guarantee will only be guaranteed until expiry of the original period guarantee period.

This guarantee covers product failures and malfunctions provided the product was used for the purpose for which it is intended and subject to installation, cleaning, care and maintenance in accordance with the information contained in these terms and conditions, in the user manual and standard practice, provided that standard practice does not conflict with the user manual.

This guarantee does not cover defects and damage caused by normal wear and tear or damage that could be the result of improper use, faulty installation or assembly, neglect, accident, misuse, or modification of the product. Unless stated otherwise by applicable law, this guarantee will not cover, in any case, ancillary costs (shipping, movement, costs of uninstalling and reinstalling, labour etc), or direct and indirect damage.

If the product is defective, we will, within a reasonable time, replace or refund. Rights under this guarantee are enforceable in the country in which you purchased this product. Guarantee related queries should be addressed to the store you purchased this product from.

The guarantee is in addition to and does not affect your statutory rights.

IMPORTANT - RETAIN THIS INFORMATION FOR FUTURE REFERENCE: READ CAREFULLY.

EN IMPORTANT - These instructions are for your safety. Please read through them thoroughly prior to handling the product and retain them for future reference.

5063022517692

V10724_5063022517692_MAND2_2324

Manufacturer:

UK Manufacturer:
 Kingfisher International
 Products Limited,
 1 Paddington Square, London,
 W2 1GG, United Kingdom

EU Manufacturer:

Kingfisher International
 Products B.V.
 Rapenburgerstraat 175E
 1011 VM Amsterdam
 The Netherlands

EN

www.diy.com
 www.screwfix.com
 www.screwfix.ie
To view instruction manuals online, visit
www.kingfisher.com/products