



Silicone 2 Ply Air Ducting

Inside Diameter	Outside Diameter	Wall Thickness	Bending Radius	Coil Weight	Coil Length
25mm	30mm	2.5mm	16mm	0.95kg	4 Metre
32mm	37mm	2.5mm	18mm	1.08kg	4 Metre
38mm	43mm	2.5mm	22mm	1.1kg	4 Metre
45mm	50mm	2.5mm	26mm	1.2kg	4 Metre
51mm	56mm	2.5mm	32mm	1.32kg	4 Metre
57mm	62mm	2.5mm	44mm	1.45kg	4 Metre
63mm	68mm	2.5mm	55mm	1.66kg	4 Metre
70mm	75mm	2.5mm	60mm	2kg	4 Metre
76mm	81mm	2.5mm	65mm	2.12kg	4 Metre
83mm	88mm	2.5mm	75mm	2.36kg	4 Metre
90mm	95mm	2.5mm	82mm	2.44kg	4 Metre
102mm	107mm	2.5mm	90mm	2.84kg	4 Metre
127mm	132mm	2.5mm	105mm	3.84kg	4 Metre
152mm	157mm	2.5mm	125mm	4.16kg	4 Metre
200mm	205mm	2.5mm	150mm	5.98kg	4 Metre

SKU - FSD

Operating Temperature
-70°C to +310°C

Peak Temperature
+350°C

Inner Layer Material
Coated Fibreglass

Reinforcement
Steel Wire Helix With Glass
Fiber Cord

Outer Layer Material
Silicone

Standard

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.