



## PVC Corrugated Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
19mm	23mm	2mm	5 Bar	15 Bar	70mm	4.1kg	30 Metre
25mm	30mm	2.6mm	5 Bar	15 Bar	70mm	9.5kg	50 Metre
28mm	33mm	2.5mm	4 Bar	12 Bar	80mm	11kg	50 Metre
32mm	38mm	3mm	4 Bar	12 Bar	90mm	11.9kg	50 Metre
38mm	44mm	3mm	3 Bar	3 Bar	110mm	14kg	50 Metre
40mm	46mm	3mm	3 Bar	3 Bar	150mm	14.7kg	50 Metre
50mm	58mm	4mm	3 Bar	3 Bar	170mm	23.5kg	50 Metre

**SKU** - PDH - Black  
CDH - Clear

**Operating Temperature**  
-10°C to +65°C

**Peak Temperature**  
+70°C

**Inner Layer Material**  
Smooth Polyvinyl Chloride (PVC)

**Reinforcement**  
High Tensile Plastic Rib

**Outer Layer Material**  
Corrugated Polyvinyl Chloride (PVC). UV Resistant.

**Standard**  
BS EN ISO 3994-2001

**Colour**  
● ○

**[View Product Online](#)**

### Hoses UK

Unit 5 Holme Bank Mills  
Station Road  
Mirfield  
West Yorkshire  
WF14 8NA

**Contact:**

01924 496111  
[web@hosesuk.co.uk](mailto:web@hosesuk.co.uk)  
[hosesuk.co.uk](http://hosesuk.co.uk)

**Hose Distribution. Simplified.**