

IS4N-40

Weathersafe Rotary Isolator Switch – 4 Pole 40A

Features & Benefits

- Four pole 40A switch
- Solid Neutral
- On load switch disconnectors
- Switch can be removed from DIN rail assembly allowing quick and easy first fix
- Interlocked front cover can only be removed when in OFF position
- Lockable switch prevents tampering
- IP65 weatherproof rating
- Tough durable thermoplastic construction
- Cable entry knockouts on enclosures



Technical Data

Operating Voltage	Up to 415V AC
Frequency	50Hz
Installation Type	Surface Mount
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP65
Setting Type	Rotary Isolator
Contact Type	Normally Open
Rotary Switch Poles	4
On Load Switch Disconnectors	Yes
Mounting Hole Centres (mm)	96 Left to Right, 135 Top to Bottom
Switch Rating	40A

Data sheet

IS4N-40

Safety / Weathersafe Isolator Switches

Cable Capacity (mm ²)	16mm ²
Cable Entry(s)	Multiple M20 Knockouts

General

Weight (g)	475.5
Height (mm)	175
Width (mm)	121
Depth (mm)	122.5
Body Construction	Polycarbonate
Product Colour	Grey / Black
EAN Number	5012483013090
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

