

STLB1000

Suretime Outdoor PIR Black

Features & Benefits

- Manual override (Pulse) for extended light on times.
- Adjustable time ON setting.
- Adjustable lux level.
- Knockouts to allow cable entry from underneath the PIR.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	8 to 12
Detection Angle	180°
Mounting Hole Centres (mm)	58
Standby Consumption	<1W
Number of Channels	1

Data sheet

STLB1000

Light / PIR Presence Detectors

Switch rating	200W LED, 1000W Halogen, 200W Fluorescent/Low Energy Lighting
ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
Lux Level	10 to 1000
Detection Range (M)	8 to 12
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 5 Units In Parallel
Cable Entry(s)	Back Entry, Bottom Entry

General

Weight (g)	119
Height (mm)	76
Width (mm)	76
Depth (mm)	87
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483014301
Guarantee Period	2 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

