

STW360

Suretime Surface Mount 360° PIR

Features & Benefits

- Surface mount PIR sensor suited for a wide array of indoor applications
- Manual override (Pulse) for extended light on times
- Adjustable time ON setting
- Adjustable lux level



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP40
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	8 Diameter
Detection Angle	360°
Mounting Hole Centres (mm)	73
Standby Consumption	<1W
Number of Channels	1
Switch rating	200W LED, 1000W Halogen, 200W Fluorescent/Low Energy Lighting

Data sheet

STW360

Light / PIR Presence Detectors

ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
Lux Level	10 to 1000
Detection Range (M)	8 Diameter
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 5 Units In Parallel
Cable Entry(s)	Back Entry

General

Weight (g)	72
Height (mm)	88
Width (mm)	88
Depth (mm)	50
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483014325
Guarantee Period	2 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

