

TGBD2

2 Hour Digital Boost Timer With Countdown Display

Features & Benefits

- 2 Hour maximum time on set in 15 minute increments
- Boost button with backlight disable feature
- Ideal for immersion heaters, room heaters, towel rails and lighting.
- Replaces existing single gang connection unit fixed appliance outlets.
- Multiple on times can be selected and viewed via the clear LED output display panel.
- Easy push button selection.
- Fits a standard flush or surface mount BS wall box.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 45°C
Ingress Protection Rating	IP20
Setting Type	Digital
Back Box Minimum Depth (mm)	25
Push Buttons	Yes (Boost Button)
Mounting Hole Centres (mm)	60
Standby Consumption	<1.3W

Data sheet

TGBD2

Time / Immersion & General Purpose Timeswitches

Number Of Channels	1
Switch Rating	13A Resistive, 200W LED, 1000W Halogen, 500W Fluorescent, 100W CFL
Shortest Switching Time	15 Minutes
Time Delay Range	15 Minutes to 2 Hours (With 15 Minute Increments)
Permanent ON Facility	No
Multiple Unit Support	No
Cable Entry(s)	Back Entry, Bottom Entry

General

Weight (g)	131
Height (mm)	85
Width (mm)	85
Depth (mm)	36
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Screws
EAN Number	5012483015445
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

