

Product data sheet



Perform

AR8200



ARRONE overhead door closing device:

- Power size: 2 to 4 adjustable by template
- Function: Closing, latching
- Cover: Slide cover
- Maximum door width: 1,100 mm (Fig 1 and Fig 61), 950 mm (Fig 6)
- Maximum door weight: 80 kg (Fig 1 and Fig 61), 60 kg (Fig 6)
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull (Fig 1), transom mount push (Fig 61): 3 | 8 | 4/2 | 1* | 1 | 3
 - Door mount push (Fig 6): 3 | 8 | 3 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634-1**. Assessed for use on 30, 60 and 120 minute timber fire doors.
- CE Marked: AD0118
- Certifire approved: CF295; DOP: HUK0020



Article number	87106856
Product ref.	AR8200-BC-SE
EAN-Code	5051358029934
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1100 mm
Maximum door weight	80 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Backcheck, template adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Trim Plate
Power size	2 to 4
Opening Angle	max. 105° opening
Mechanism dimensions and fixing centres	207x55x38.5 mm; centres 97x197x39 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	SE Silver Enamel
Finish of the cover	SE Silver Enamel
Arm finish	SE Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	6