

Dryzone System Mould-Resistant Emulsion Paint

Product Description

An excellent, premium quality, low odour mould-resistant coating guaranteed to protect against unsightly and unhygienic black mould even when there is persistent condensation. The unsurpassed performance of Dryzone System Mould-Resistant Emulsion Paint is achieved by combining modern paint technology with advanced paint-film protection. It is fully washable and resistant to the effects of condensation when the coating is fully dried out.



Areas of Application

Ideal for walls and ceilings in private and social housing and a wide range of public and commercial buildings.

Benefits

- Lasts for at least **5 years**: prevents the recurrence of black mould
- Quick drying with no over-painting problems; compatible with all known paint finishes
- Easy to use and cost effective

The Dryzone System Mould-Resistant Emulsion Paint will help compliance with Section 82 (Statutory Nuisance), Chapter 43 of the Environmental Protection Act 1990, either used alone or part of various strategies to prevent condensation and mould growth in both private and public tenanted accommodation.

Safeguard Europe Ltd offers the reassurance of a full technical support and advisory service for condensation and mould growth to assist with specification queries or general problems.

Surface Preparation

Preparation is straightforward and very similar to normal good decorative practice.

1. Remove any loose material such as old paint, grease, dirt, mould or defective wallpaper. Soluguard Multi-Surface Biocide can be used for wetting mould-contaminated wallpaper prior to removing it.
2. Make good any defects in the surface and rub down to a smooth finish.
3. Wash and clean all surfaces (walls, ceilings, window frames and joinery) using Soluguard Multi-Surface Biocide. If necessary clean badly affected areas a second time.
4. Allow to dry thoroughly.
5. If necessary, apply an appropriate primer or sealer to new, unprimed or porous plaster and wooden surfaces or bare metal.
6. For new or porous plaster surfaces use Dryzone System Mould-Resistant Emulsion Paint thinned up to 10% with clean tap water as normal good practice. Allow to dry thoroughly.

Application

1. Apply Dryzone System Mould-Resistant Emulsion Paint using brush or roller.
- 2. Stir thoroughly before use.**
3. Apply two coats of Mould-Resistant Emulsion Paint allowing sufficient drying time between coats.
4. Clean equipment with clean tap water before the paint dries.
- 5. Mould-Resistant Emulsion Paint must not be covered with any other paint or wallpaper.**

N.B. If an unfinished, textured wallpaper (blown vinyl, woodchip) or similar is to be used then it should be hung after Soluguard Multi-Surface Biocide has fully dried. The wallpaper should be coated with Dryzone System Mould-Resistant Emulsion Paint as above. If in doubt, please contact our Technical Department for advice.

Product Information

Dryzone System Mould-Resistant Emulsion Paint is supplied in 2.5 and 5 litre HDPE containers. Average coverage rate is 10-12m² per litre but an extra allowance should be made for rough or porous surfaces. Touch dry in 1 hour and recoatable after 2-4 hours dependent on conditions.

Store above 5°C in dry conditions. Keep the container tightly sealed and away from children. Correctly stored, the unopened product has a shelf life of 12 months.

Technical Data

Coverage	10 – 12 m ² per litre
Colours	Brilliant White, Magnolia and selected pastel colours. Specific colours may be supplied depending upon requirements.
Thinning	Use clean tap water but do not exceed 10% by volume.

Health & Safety

Refer to Safety Datasheet (SDS) before using the product.

Quality & Environment

Dryzone System Mould-Resistant Emulsion Paint is supplied in accordance with ISO 9001 and ISO 14001 quality and environmental management systems.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.