

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.2024

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier

- Trade name: **Stormsure PVC Glue**

- Article number: R069474-00

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- **Application of the substance / the mixture** Adhesives

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Stormsure Ltd

Haynes' Yard, Swaffham Road, Longmeadow

- Cambridge, CB25 9EZ, UK

Tel.: +44 (0)3333441500

www.stormsure.com

- Informing department:

(department: C-U Quality- and Environmental management center)

Tel.: +44 (0)3333441500

E-Mail: info@stormsure.com

- 1.4 Emergency telephone number:

In case of poisoning:

GBK-EMTEL International

Tel.(24h): +49(0)6132/84463 (all languages)

In case of transport accidents:

Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 / GBK)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Additional information:** The classification resulted from the calculation method of CLP-regulation.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 1)

- Hazard pictograms

GHS02 GHS07

- Signal word Danger**- Hazard-determining components of labelling:**butanone
acetone
ethyl acetate**- Hazard statements**H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.**- Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403 Store in a well-ventilated place.

- Additional information:

EUH208 Contains 3,4-epoxycyclohexylmethyl 3,4-epoxycyclohexane carboxylate. May produce an allergic reaction.

- 2.3 Other hazards

In the event of a large-scale use of the product, ignition sources in the immediate proximity and in low-lying areas, such as welding equipment, bells, heating elements, refrigerators, storage heaters etc. should be switched off! Erect warning signs warning of the hazardous risk of explosive atmosphere!

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures**- Description:** Mixture of several substances**- Dangerous components:**

CAS: 78-93-3	butanone	25-50%
EINECS: 201-159-0	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: Stormsure PVC Glue

(Contd. of page 2)

CAS: 67-64-1 EINECS: 200-662-2	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-20%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	<12.5%
CAS: 2386-87-0 EINECS: 219-207-4	3,4-epoxycyclohexylmethyl 3,4-epoxycyclohexane carboxylate Skin Sens. 1, H317	<0.5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- After inhalation

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness bring patient into a stable side position for transport.

- After skin contact

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

- **After swallowing** Do not induce vomiting; call for medical help immediately.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents

Water spray

Alcohol-resistant foam

Fire-extinguishing powder

Carbon dioxide

- **For safety reasons unsuitable extinguishing agents** Water with full jet.

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters

- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:** Pick up mechanically.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 3)

- 6.4 Reference to other sections

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from frost.
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.
Store in dry conditions.
- **Storage class (according german VCI-concept):** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **8.1 Control parameters**

- Components with limit values that require monitoring at the workplace:

butanone	
WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
IOELV (European Union)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
acetone	
WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (European Union)	Long-term value: 1210 mg/m ³ , 500 ppm
ethyl acetate	
WEL (Great Britain)	Short-term value: 400 ppm Long-term value: 200 ppm

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 4)

IOELV (European Union)	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
------------------------	--

- DNELs

78-93-3 butanone

Inhalative	worker (long-term exposure/systemic)	600 mg/m ³
------------	--------------------------------------	-----------------------

67-64-1 acetone

Inhalative	worker (long-term exposure/systemic)	1,210 mg/m ³
------------	--------------------------------------	-------------------------

141-78-6 ethyl acetate

Inhalative	worker (long-term exposure/systemic)	734 mg/m ³
	worker (long-term exposure/local)	734 mg/m ³

- Ingredients with biological limit values:

butanone

BMGV (Great Britain)	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
----------------------	---

- Additional information:

The homogenous mixing of this product is safeguarded by continual physical testing. Raw materials which formerly had dust-like properties are completely incorporated into the liquid / paste-like mass. Subsequently, possible TLVs for solid substances are not given, as there is no more danger of inhaling these substances (when dealing with this mixture)!

- 8.2 Exposure controls

- Personal protective equipment

- General protective and hygienic measures

The usual precautionary measures should be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of the work.

Immediately remove all soiled and contaminated clothing

- Breathing equipment:

Not required with good ventilation and/or adequate extractor facilities

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:

A2 (DIN EN 14387 / DIN EN 141)

- Protection of hands:

Direct contact with the chemical preparation must be avoided by organizational measures. Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

Compliance with the stated penetration time (starts with the first product contact) must be ensured!

The gloves need to be disposed of after the penetration time and new gloves used!

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 5)

- For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the "Barrier 02-100" underglove from Ansell (penetration time 480 min).

- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Fluorinated rubber (Viton) [0.7mm - penetration time 15 min]

- As protection from splashes gloves made of the following materials are suitable:

Recommended for protection from splashes: disposable nitrile gloves (minimum thickness 0.12 mm) with long cuffs. After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

- Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form:	Fluid
Colour:	Colourless
- Odour:	Solvent-like
- Odour threshold:	Not determined.

- Change in condition

Initial boiling point and boiling range: 56 °C

- Flash point: -20 °C

- Ignition temperature: 460 °C

- Explosion limits:

Lower:	1,8 Vol %
Upper:	13,0 Vol %

- Vapour pressure at 20 °C: 240 hPa

- Specific gravity at 20 °C: 0,78 g/cm³

- Vapour density: Not determined.

- Evaporation rate: Not determined.

- Solubility in / Miscibility with

Water: Partly soluble

- Partition coefficient: n-octanol/water: Not determined.

- Viscosity:

dynamic at 20 °C: 4300 mPas (Brookfield)

- Solvent content:

Organic solvents:	77,0 %
VOC (EU):	600.6 g/l

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 6)

VOC (EU): 77.00 %

VOC (CH): 77.00 %

Solids content: 23,0 %

- 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
In case of fire, the following substance(s) may occur:
Hydrogen chloride (HCl)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- LD/LC50 values that are relevant for classification:

78-93-3 butanone

Oral	LD50	2,500 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rbt)
Inhalative	LC50/4 h	40 mg/l (mus)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rbt)

141-78-6 ethyl acetate

Oral	LD50	4,935 mg/kg (rbt)
Inhalative	LC50/4 h	1,600 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 7)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal in accordance with official regulations
- **EWC-Code(s):**

To be treated as industrial waste: do not dispose of in or on soil, in watercourses or bodies, or through a sewage system. These EU refuse code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances listed under item 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application:

080409* waste adhesives and sealants containing organic solvents or other dangerous substances
080410 waste adhesives and sealants other than those mentioned in 080409

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances
08 04 12 adhesive and sealant sludges other than those mentioned in 080411

Soiled waste packaging:

15 01 10* packaging containing residues of or contaminated by dangerous substances.

Clean waste packaging:

15 01 01 paper and cardboard packaging
15 01 02 plastic packaging
15 01 04 metallic packaging

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020


Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 8)

SECTION 14: Transport information

- 14.1 UN-Number - ADR/RID/ADN, IMDG, IATA	UN1133
- 14.2 UN proper shipping name - ADR/RID/ADN - IMDG - IATA	1133 ADHESIVES ADHESIVES (ETHYL METHYL KETONE (METHYL ETHYL KETONE), ACETONE) ADHESIVES
- 14.3 Transport hazard class(es) - ADR/RID/ADN, IMDG, IATA	
	
- Class - Label	3 Flammable liquids. 3
- 14.4 Packing group - ADR/RID/ADN, IMDG, IATA	II
- 14.5 Environmental hazards: - Marine pollutant:	No
- 14.6 Special precautions for user - Danger code (Kemler): - EMS Number: - Stowage Category	Warning: Flammable liquids. 33 F-E,S-D B
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
- Transport/Additional information:	
- ADR/RID/ADN - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- Transport category - Tunnel restriction code - Remarks:	2 D/E (Packing group III, if content of packaging ≤ 450l, according 2.2.3.1.4 ADR)
- IMDG - Limited quantities (LQ)	5L

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: **Stormsure PVC Glue**

(Contd. of page 9)

- Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml (Packing group III, if content of packaging ≤ 30l, according 2.3.2.2 IMDG)
- Remarks:	
- IATA	
- Remarks:	(Packing group III, if content of packaging ≤ 30l, according 3.3.3.1.1 IATA)
- UN "Model Regulation":	UN 1133 ADHESIVES, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Information about limitation of use:**
Employment restrictions concerning young persons must be observed.
- **Disturbance regulations:**
Critical quantity values according to the regulations on accidents should be adhered to.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

For industrial use only.

- **Legend of H- and R-phrases, concerning the in chapter 3 mentioned substances (marking of product please see chapter 2)**
H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Department issuing SDS:**
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.12.2020

Version number 3

Revision: 11.07.24

Trade name: Stormsure PVC Glue

(Contd. of page 10)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB