Product Information Sheet:

Floor Paint & Floor Paint Anti Slip 2.5L & 5L



Available in 190 RAL shades



TOUGH, GLOSSY, POLYURETHANE FORMULA FOR CONCRETE FLOORS.
Floorsaver Floor Paint dustproofs, seals and protects internal concrete floors. Two coats provide a glossy, easily cleaned finish. It can be applied to bare concrete or existing well bonded paint.

- Greatly improves the appearance of drab concrete
- Tough enough for warehouses, workshops and general use
- Single pack – just use as much as you need and replace the lid if you've got any left over
- Easy roller application
- Choose Floor Paint Anti Slip for wet or slippery areas
- Resists spillages of oils and grease
- Suitable for concrete, wood and most metals
- 2.5L covers up to 20m^2 per coat
- 5L covers up to 40m^2 per coat

HERE'S HOW TO USE IT:

Step 1 - Preparation:

- On bare, reasonably clean concrete wash with Floorsaver Floor Etcher. This cleans and keys the surface. On greasy or previously painted floors clean with Floorsaver Cleaner & Degreaser, scraping off any loose paint, dust or dirt. New concrete should be at least 2 months old and always washed with Floorsaver Floor Etcher to reduce alkalinity.

Step 2 – Repairs

- Fill holes using Floorsaver Pourable Concrete Filler.

Step 3 - Application:

- Check the floor is dry before painting and that the temperature is a minimum of 15°C.
- Stir the paint thoroughly.
- Do not thin.
- Tip into a roller tray.
- Cut in around edges with a brush.
- Apply to the floor area using a paint roller, working well into the surface. Bare concrete should be sufficiently porous to allow the first coat to sink in.
- Clean equipment with White Spirit.

For Floor Paint Anti Slip:

- Add all the anti-slip aggregate for 5L units or half for 2.5L, stirring thoroughly. Use immediately. The aggregate becomes more visible as the paint dries, and two coats are recommended for a consistent anti-slip finish.

DRYING TIMES:

RECOAT	16 hours at 15°C - 20°C. The second coat should be applied within 5 days of the first coat.
TOUCH DRY	10 hours at 15°C - 20°C
LIGHT FOOT TRAFFIC	24 hours at 15°C - 20°C
FULL USE	36 hours at 15°C - 20°C. Please check that the paint has fully cured before putting into full use.

WE DON'T RECOMMEND:

- Using this product in areas where cars are parked – instead use Floorsaver Epoxy Floor Paint.
- Applying to self-levelling floor screeds.
- Applying to concrete contaminated with oil, grease, fats or wax.
- Applying to hard, smooth, very dense or power floated concrete where the paint can't soak into the surface. If in doubt tip a cup of water onto the floor and see if it disappears.

SHELF LIFE:

3 years, if unopened and should not be allowed to freeze.

SAFETY:

- Material Safety Data Sheets are available.
- Product labels provide general safety information.

ORDERING:

Please place your order direct from us online using a debit or credit card. We want you to enjoy using our products and achieve a really good result.

If you have any comments please contact us using the details below.

Sales & Technical Support

UK:	0345 450 9888	info@floorsaver.co.uk	floorsaver.co.uk
IE:	0818 543 250	info@floorsaver.ie	floorsaver.ie

©floorsaver April 2026