

Standard Garden Lawn Roller

GLR101


KCT

Parts Required: (Not supplied)

Water / Sand / Cement

Parts:

1. 4x Nut
2. 4x Bolts
3. 4x Washers
4. 2x Large Washers
5. 2x Split Pin
6. 1x Metal Bottom Brace
7. 1x Cross Bar
8. 1x Handle
9. 1x Drum



Assembly

- Attach the metal bottom brace (6) to the Drum using 2 large washers (4) and 2 split pins (5).
- Attach the handle (8) to the metal bottom brace (6) using 2 bolts, washers and nuts (2,3,1).
- Attach the cross bar (7) to the metal bottom brace (6) using 2 bolts, washers and nuts (2,3,1).
- Tighten all 4 nuts & bolts securely.
- Remove cap on the drum (9) and fill carefully with either sand, water or concrete (not included) mix until completely full. Replace cap securely.

Imported by:

KCT Leisure
Glebe Farm,
Old London Road,
Copdock, Ipswich,
Suffolk, IP83JN,
United Kingdom

Application

Use the law roller when seeding a new lawn or after cutting to improve the overall appearance of the lawn. Rolling will spread the grass roots giving thicker coverage. Rolling is advised everytime the lawn is cut.

Safety Warning

When using the lawn roller, it's essential to keep your hands and feet clear of the heavy drum. Special care is necessary when using the lawn roller on a slope. This product is not a toy and is not suitable for use by children.