

ANNIE SLOAN WALL PAINT

PRODUCT INFORMATION SHEET

PRODUCT DETAILS



WASHABLE & WIPEABLE



QUICK DRYING



EXPERTLY TESTED



WATER BASED



MATT FINISH



PIGMENT RICH

Suitable for interior use on walls and ceilings

SHEEN LEVEL

- Matt (less than 5% sheen)

VOC LEVELS

- Low in VOCs
UK/EU/AUS/NZ <18.5g/L

SAFETY / AIR RATING

- Certified as Toy Safe (EU Toy Safety Directive BS EN 71-3:2013).
- EU INDOOR AIR RATING: A



INTRODUCTION

Annie Sloan Wall Paint is a whole new paint formula, specifically designed for walls, from Chalk Paint inventor Annie Sloan. It gives premium colour pay-off in 32 beautiful colours and provides a durable, wipe-clean finish in one step.

ON EXISTING PAINT FINISH:

- Ensure surface is sound, clean and dry and free from any dirt, dust or other contaminants.
- Sand back any previous unsound paint layers before you begin.
- When painting over vinyl silk, key the surface with sandpaper or prime with a water based primer to avoid cracking in the finish.
- On new or unpainted lining paper: apply a diluted mist coat in the same way as if painting a plaster wall. Dilution rate depends on porosity of surface.
- Not recommended for painting lime plaster or other surfaces that require a breathable finish. For this we would recommend Chalk Paint, although it will not have the same wipe clean properties as Annie Sloan Wall Paint.



120ML



SIZES AVAILABLE

- UK/EU/AUS/NZ:
2.5L (0.66 US Gal / 120ml (4.06 US Floz)

COVERAGE

UK/EU/OZ/NZ:

- 2.5 Litres is enough to cover approximately 27.5 square metres (296ft²).
- 120ml is enough to cover approximately 1.32 square metres (14.2ft²).

Actual coverage is dependent on surface porosity and application.

PREPARATION

On new or unpainted plaster or dry walls:

- Allow 4 weeks for newly applied plaster to fully cure, allowing for slower curing caused by environmental conditions.
- Prime the wall by thinning the paint with water and applying as a mist coat. Dilution rate depends on porosity of surface. Test diluted paint on a small, inconspicuous patch area to determine the required ratio of water to paint.

APPLICATION

- Stir well before use.
- Apply using a high quality brush or roller.
- Two coats recommended.
- Darker colours may require an undercoat or an extra coat to achieve depth of colour.
- Do not paint in temperatures below 10 °C or above 30 °C. Painting in humid or colder conditions will prolong drying time. Allow finish to thoroughly dry before exposing to wet or humid conditions.

Application by brush - Stir thoroughly before use. Apply with an appropriately sized, good quality synthetic or synthetic/bristle mix brush. Start at the top of the wall and work down. Do not try to paint over an area that has partially dried.

CONTINUED OVERLEAF..



www.AnnieSloan.com

Annie Sloan is a registered trade mark of Annie Sloan Interiors Ltd. in the US. 'ANNIE SLOAN' is a registered trade mark of Annie Sloan Interiors Ltd. in the UK, EU, CH, US, CAN, AUS, NZ, ZA, CN, KR, MX, AZ, IN, IR, JP, RU, SG, TR & UA. ©2022 ANNIE SLOAN INTERIORS LTD. 1 Ashville Way, Oxford, OX4 6TU. UK. (+44) 1865 713089.

ANNIE SLOAN WALL PAINT

PRODUCT INFORMATION SHEET

Application by roller - Stir thoroughly before use. Using a medium pile roller, roll the paint onto the wall in large V-shaped strokes. Fill in the area by spreading out evenly. Work in small sections to maintain a wet edge. Avoid going back over paint which has already begun to dry.

DRYING TIME / REAPPLICATION

- Touch dry in 40 minutes.
 - Recoat in 1.5 hours (temperature and humidity dependent).
 - Allow up to 14 days to reach full hardness and durability.
 - Allow extra drying time when painting in bathrooms. Surfactant leaching can occur when newly painted surfaces are exposed to humidity or steam before the paint has had chance to properly dry.
-

CLEAN UP

- Wash brushes or rollers in soap and water immediately after use.
-

AFTERCARE

- The full curing time should be observed before cleaning or scrubbing the finish. This can take up to two weeks and is dependent on site specific conditions. After this time, paintwork can be washed with a mild soap solution and a soft cloth.
-

STORAGE / SHELF LIFE

- Store in a cool and dry place, preferably at a constant temperature.
- To maximize shelf life, decant used tins that are less than half full into smaller, tightly sealed containers.
- Please use within one year of purchase.

