

Roof Repair Coating (high performance)





Save money on roof repair with this high-performance roof repair coating. Acrylic resin formulation provides instant shower protection with just one coat.

- ✓ Low odour, low VOC acrylic resin system for use on flat and pitched roofs, bitumen felt, asphalt, concrete, brickwork, etc.
- ✓ Also ideal for waterproofing of cracked roof tiles and split guttering.
- ✓ Cold applied, use straight from the can. Flexible formulation expands and contracts with heat.



INSTANT PROTECTION AGAINST WATER INGRESS

Flexible, durable fibre-filled solvent-based roof coating that can be used all year round. Supplied ready for use. Cold applied. Apply with brush or roller. Suitable for all types of roofs, including flat, pitched, bitumen, guttering, brickwork, concrete, felt, metal and fibreglass.



PHYSICAL PROPERTIES

Flash point	n/a
Coverage	18m ² /litre
Appearance	As per colour
Solid content	8%
Viscosity @ 23°C	17 seconds
Touch dry	30 minutes
Odour	Mild solvent
UN number	UN1263

SURFACE PREPARATION

Remove all loose contamination from roof such as chippings, moss, lichen, dust, and dirt. Where growth was present the area should be treated with fungicidal wash in accordance with manufacturer instructions.

Metal surfaces should be cleaned with a wire brush to remove rust and provide a key. Splits or blisters should be cut and sealed prior to application. Always try a test patch prior to large scale application.

APPLICATION

Apply generously using a brush or roller at a rate of 1-2 kg per m², dependant on the substrate.

Recommended application temperature is between 5 - 25°C. Roof Repair Coating will thicken at lower temperatures which can affect coat weight. Can be applied to damp surfaces.

High fibre content means cracks of several mm wide can be filled. Larger voids should be filled with a suitable tape reinforcement such as a duct tape.

DRYING

Will be waterproof immediately after application. Drying time is 2-3 days depending on atmospheric conditions.

STORAGE GUIDELINES

Store indoors, away from direct sunlight in original container, in a dry place at temperature between 5 and 40°C.

Keep out of reach of children.

Shelf life is 12 months under above mentioned storage conditions.

FIRST AID

EYE CONTACT

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

INHALATION

Seek fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

SKIN CONTACT

Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention, show the container label. Protection of first aiders: No action shall be taken involving any personal risk or without suitable training.



TradeCoatings[®]

The advice and information given in this data sheet is given freely and in good faith and is based upon data that we believe is reliable. The data herein is based on extensive laboratory testing and experience, but we cannot test for every eventuality. It remains the customers responsibility to ensure the product is fit for intended purpose. Trade Coatings cannot guarantee anything but the quality of the product and cannot be held responsible for results obtained.