

# Floor Lacquer (single pack)

For internal wooden floors. New technology single-pack solvent-based lacquer providing a beautiful, tactile, and durable finish.

Available in a range of finishes from matt to high gloss.

Perfect for lower traffic areas.

Pre-Catalysed (single pack) formulation for use straight out of tin, no pre-mixing required.



- ✓ Moisture and chemical resistant
- ✓ Isocyanate free
- ✓ Hydrocarbon free

## PHYSICAL PROPERTIES

Flash point	21°C
Coverage	12m <sup>2</sup> /litre
Appearance	Clear / milky
Solid content	40%
Viscosity @ 23°C	24+2 seconds
Touch dry	20 to 30 minutes

FINISH	GLOSS @ 60'
Matt	10%
Eggshell	20%
Silk	40%
Gloss	90%

## **SURFACE PREPARATION**

Remove all loose contamination from substrate such as dust and dirt. All surfaces should be grease free and sanded ready to be coated. Wipe the surface with White Spirit.

Ideal for use over Trade Coatings Wood Stain, or coat-on-coat application with a light sand in between each coat.

If using on MDF we recommend the use of Trade Coatings MDF Sealer first as a base coat.

## **APPLICATION**

Suitable for brush, roller, or spray application. Allow at least 30 minutes drying time before sanding and overcoating (longer in temperatures below 18°C).

For airless spray use a 1.7mm or 1.8mm nozzle. If necessary, thin with Trade Coatings Thinner.

## **CURING AND AFTERCARE**

Achieves full durable hardness over a period of a few weeks. For cleaning the surface during this period use a damp soft cloth or mop.

## **STORAGE**

Store indoors, away from direct sunlight in original container, in a dry place at temperature between 5 and 40°C.

Keep out of reach of children.

Shelf life is 24 months under above mentioned storage conditions.

## **SAFETY**

Pre-catalysed lacquers are skin and eye irritants and sensitisers. It is extremely important to wear protective gloves and eye protection when handling. Spills or splashes must be removed immediately – if allowed to dry, material can only be removed mechanically or with heat and/or harsh chemicals.

Environmentally hazardous - do not allow wet product to enter water courses, drains, sewers or the general environment.

For professional use only.

## **FIRST AID**

### **EYE CONTACT**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

### **INHALATION**

Seek fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

### **SKIN CONTACT**

Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

### **INGESTION**

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention, show the container label. Protection of first aiders: No action shall be taken involving any personal risk or without suitable training.



**TradeCoatings<sup>®</sup>**

The advice and information given in this data sheet is given freely and in good faith and is based upon data that we believe is reliable. The data herein is based on extensive laboratory testing and experience, but we cannot test for every eventuality. It remains the customers responsibility to ensure the product is fit for intended purpose. Trade Coatings cannot guarantee anything but the quality of the product and cannot be held responsible for results obtained.