

High-Build Primer (white)

Very high-build solvent-based, single pack primer for internal use.
Provides a smooth and level base prior to painting.
Fast drying. Easy to apply and sand back.

PERFECT FOR:

- ✓ Kitchens
- ✓ Shop displays
- ✓ Chip board
- ✓ Engineered wood
- ✓ Furniture
- ✓ MDF
- ✓ Soft wood
- ✓ Cabinetry
- ✓ Plywood
- ✓ Hard wood



PHYSICAL PROPERTIES

Flash point	23°C
Coverage	varies depending on substrate and application method
Appearance	White
Solid content	58%
Viscosity @ 23°C	35 seconds
Drying time	Recoatable in 10 – 20 minutes
Odour	Mild solvent
UN number	UN1263

SURFACE PREPARATION

Ensure substrate is clean, dry, dust-free and free from grease, oil, silicones, and other surface contaminants.

APPLICATION

Suitable for brush, roller, or spray application. Allow at least 30 minutes drying time before sanding and overcoating (longer in temperatures below 18°C).

For airless spray use a 1.7mm or 1.8mm nozzle. If necessary, thin with Trade Coatings Thinner.

STORAGE

Store indoors, away from direct sunlight in original container, in a dry place at temperature between 5 and 40°C.

Keep out of reach of children.

Shelf life is 12 months under above mentioned storage conditions.

PRECAUTIONS FOR SAFE HANDLING

- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use personal protective equipment as required.
- Get medical advice/attention if you feel unwell.

FIRST AID

EYE CONTACT

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

INHALATION

Seek fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

SKIN CONTACT

Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION

If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention, show the container label. Protection of first aiders: No action shall be taken involving any personal risk or without suitable training.



TradeCoatings®

The advice and information given in this data sheet is given freely and in good faith and is based upon data that we believe is reliable. The data herein is based on extensive laboratory testing and experience, but we cannot test for every eventuality. It remains the customers responsibility to ensure the product is fit for intended purpose. Trade Coatings cannot guarantee anything but the quality of the product and cannot be held responsible for results obtained.