

This **Liquida** 4 in 1 kitchen tap will provide near boiling hot water and filtered water for drinks and cooking, as well as standard hot and cold water for everyday kitchen tasks.

Temperature from the boiler tank can be adjusted from 75 to 98 degrees Celsius.

The water tap connects to standard hot and cold feeds, with a separate line from the tank to supply the 'boiling' water.

Water from 75 to 98 degrees Celsius is immediately available saving you time in your busy day.

If you boil hot water many times a day you can save by using a boiling hot water tap instead of a kettle. You can also save energy by using the tank (which provides boiling hot water from a cold feed).

Households misuse water in both small and significant quantities. For example, if you boil twice as much water as you need or when you turn on the tap and wait for the water to warm up. This kind of waste can be avoided by the use of a boiling hot water tap.

Make a cup of tea or filtered coffee in a hurry. Prepare the food. Rinse out used dishes, this tap can do it all.

Have peace of mind knowing that each tap has a child-proof safety handle that is spring-loaded. The whole spout of the tap has been insulated. Most importantly, unlike a kettle or pan, it will not tip over.

### **Tap Details**

Colour: Brushed Brass

Material: Brass

Installation Type: Sink Or Deck Mounted

Certification: WRAS

Guarantee: 3 Years

### **Tap Specification**

Tap Tails Included: Yes

Style: Contemporary

Min working pressure: 1 bar

Max Working Pressure: 3 bar

Flow Type: Tri Flow

Number Of Tap Holes Required: 1

Handle Type: Lever

Swivel Spout: Yes

Inlet: 1/2" BSP Flexi Tails  
Tap Hole Diameter: 35mm  
Child Lock: Spring Lock Mechanism  
Instant Hot Water & Filtered Water Handle: Left Side  
Standard Hot & Cold Handles: Right Side  
Height (mm): 364  
Width (mm): 150  
Length/Depth (mm): 224  
Tap Weight (Kg): 1.6

### **Digital Tank Information**

Construction material: ABS/Glass  
Installation Type: Stand Alone  
Colour: Matt black  
Certification: WRAS  
Guarantee: 2 Years

### **Digital Tank Specification**

Connection: 1 3/8" BSP Female to 1/2" BSP Male adaptor  
Connection 2: 3/8" BSP Female to quick connection adaptor  
Tank capacity: 2.4ltr  
Rated Input: 1.5 Kw  
Rated Voltage: 220-240V ac, 50HZ  
Standby Power: 2.2W  
IPX Classification: IPX4  
Static Bar Pressure: 1 Bar  
Dynamic Bar Pressure: 1.5 – 5 Bar  
Optimum working pressure: 1 Bar Min to 3 Bar Max  
Plug Type: Fused 13amp 3 pin plug  
Power Cord Length (mm): 910  
Function type: Touch Screen Digital Interactive Control  
Temperature Control Guarantee: 75-98°C  
Height (mm): 330  
Width (mm): 230  
Length/Depth (mm): 210  
Weight (Kg): 4.5