

## SOLYX®

## SXD-4230 DichroShards



### Product Details

A shimmering and beautiful, dichroic cut glass film, that shifts through a rainbow of colours from a change in light or movement. An excellent privacy film obscuring direct visibility and allowing excellent light transmission. Adhesive backed.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

### Specification

<b>Product Code</b>	SXD-4230
<b>Film Type</b>	Vinyl/Polyester
<b>Adhesive Type</b>	Pressure-sensitive
<b>Usage</b>	Interior or Exterior
<b>Available Roll Width(s)</b>	35"
<b>Thickness</b>	305 micron
<b>Visible Light Transmission</b>	75%
<b>UV Transmission</b>	7%
<b>Infrared Transmission</b>	75%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit [www.glassfilms.eu/validate](http://www.glassfilms.eu/validate) to validate.



### Product Construction

#### Face Film

254 micron Vinyl/ 51 micron Polyester

#### Adhesive

Adhesive Clear, pressure-sensitive

#### Release Liner

Transparent Synthetic

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)