



## CD-437 - Linear Drainage

### KEY FEATURES

- CE and UKCA marked and fully certified to BS EN 1433:2002
- Lightweight
- Heat resistant (Ideal for tarmac edging)
- Locking bar grating retention
- Matching Silt box available (CD 438)
- Narrow-slot "heel-guard" Ductile iron grating
- Where water-tight Clark Drain channel is mandatory, a suitable mastic sealant such as Sikaflex (219i, 11FC) or Geocel (945, Marine) should be used when fitting channels together (and accessories)
- Compatible end cap available (CD 436)
- Load Class C250



## CD-437 - Specifications

Product Weight (Kg)	9
Channel Material	Polypropylene Grade AP9
Grating Material	Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:2011
Channel Length(mm)	1000
Channel Width(mm)	100 Internal 147 External
Channel Height(mm)	128 Internal 158 External
Grating Slot width(mm)	6
Waterway Area (cm <sup>2</sup> )	180
Grating Qty and size per channel(mm)	2 X 500



CD437/V0.1/30-10-2023

Due to our continuous product improvement program features and sizes may be subject to change without notice.

CLARK DRAIN, STATION ROAD, YAXLEY, PETERBOROUGH, PE7 3EQ, TEL. +44 (0) 1733 765317