

DECOCORK Cork Insulating Paint



1. Product Description

DECOCORK Cork Insulating Paint is a high-build, water-based interior coating formulated with natural cork granules. It is designed to help improve the thermal comfort of cold internal wall surfaces and support the reduction of surface condensation when applied correctly.

The product works by forming a breathable cork layer that helps gently raise surface temperature while allowing moisture vapour to pass through the wall.

2. Intended Use

DECOCORK is suitable for:

- Internal walls and ceilings
- Cold or condensation-prone internal surfaces
- Residential and light commercial interiors
- Bedrooms, living rooms, hallways and home offices

3. Limitations & Important Information

- This product does not kill, remove or prevent mould.
- Any existing mould must be cleaned and removed prior to application.
- Not suitable for walls affected by rising damp, penetrating damp or active water ingress.
- Not suitable for external use.
- Performance depends on surface condition, correct application, heating and ventilation.

4. Surface Preparation

- Correct preparation is essential.
- Ensure the surface is clean, dry and structurally sound.
- Remove loose or flaking paint, wallpaper, dust and grease.
- Clean any visible mould using a suitable mould cleaner and allow the surface to dry fully.
- Repair cracks or defects and allow repairs to cure.
- Highly porous, chalky or friable surfaces should be stabilised with a suitable primer and allowed to dry before application.

5. Tools Required

- Medium-pile roller or suitable paint brush
- Paint tray
- Clean mixing paddle or stirrer
- Clean water for tool cleaning

6. Mixing

- Stir thoroughly before use to evenly distribute the cork granules.
- Do not dilute unless specifically advised.

- Re-stir occasionally during use to maintain consistency.

7. Application Instructions

- Apply the first coat evenly using a roller or brush.
- Allow the coat to dry fully before applying the next coat.
- Apply a total of three (3) coats to build up the cork layer effectively.
- Ensure adequate ventilation during application and drying.
- Drying times will vary depending on temperature, humidity and airflow.

8. Overcoating

- Once fully cured, DECOCORK may be over-painted with a breathable interior paint if a different colour or finish is required.
- Avoid non-breathable coatings, as these may reduce performance.

9. After Application

For best results:

- Maintain normal household heating and ventilation
- Avoid excessive moisture build-up (e.g. drying clothes indoors without ventilation)
- Monitor condensation levels, particularly during colder months

10. Finish & Appearance

Natural matt finish

- Light surface texture visible due to cork content
- Texture variation is a normal characteristic of the product

11. Cleaning & Maintenance

- Clean tools with warm water immediately after use
- Once cured, surfaces may be gently wiped with a damp cloth
- Do not use abrasive cleaners

12. Storage

- Store in a cool, dry place
- Protect from frost and direct sunlight
- Ensure the container is sealed when not in use

13. Safety Information

- Water-based, low odour formulation
- Avoid contact with eyes and prolonged skin contact
- In case of eye contact, rinse immediately with clean water
- Keep out of reach of children
- Wash hands after use

14. Disposal

Dispose of unused product and empty containers responsibly, in accordance with local authority guidance.



Manufacturer / Distributor (UK Responsible Party):

ECOPROCORK
Unit 3.11, Cannock Chase Enterprise Centre
Walkers Rise, Rugeley Road
Hednesford, Cannock
WS12 0QU
United Kingdom

Email: info@ecoprocork.com
Website: www.ecoprocork.com



Document version: DECOCORK-IM-UK-01
Date: February 2026