



TIKKURILA

SPAKKELI PUUKITTI

WOOD FILLER

- DESCRIPTION** Water-borne special putty. After drying, Spakkeli Puukitti mimics the colors of an untreated wood surface. Filling capacity max. 2 mm.
- RECOMMENDED USES** Furniture, doors, panel walls and ceilings and other wood surfaces.
- PRODUCT FEATURES** For filling holes in interior wood surfaces. The filler-treated hole is suitable to be lacquered, painted or stained.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



SPAKKELI PUUKITTI

TECHNICAL DATA

Colour Shades	Colors: Pine, Birch, Oak, Beech, Dark Mahogany
Can sizes	0.2 l, 0.5 l
Application method	Apply with a spatula.
Drying time	A thin filling layer can be sanded after approx. 4 hours and deeper filling layers the following day.
Density (kg/l)	1.8 kg/l, ISO 2811
Volume solids (%)	67
Storage	Protect from frost.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

SPAKKELI PUUKITTI

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry, the temperature at least +5°C and the relative humidity of the air below 80%.

Surface preparation

Remove dirt, dust and loose material from the surface.

Application

Clean the surface of any dirt. Remove any dust and loose material by brushing. Apply Spakkeli Puukitti with a spatula. Thin with water, if necessary. Fill larger cracks preferably two or more times. Sand the surface and remove the sanding dust.

The surface can be stained with Parketti-Ässä, Akvi Color or Dicco Color stain.

Surface treatment with clear or tinted Kiva furniture lacquer, Unica Super or Paneeli-Ässä, Parketti-Ässä Lattialakka, Merit catalyzed lacquer or Akvilac FD range of products depending on the surface.

Note the possible difference in the staining of a wood surface and a cement surface during surface treatment.

Note

Note the different coloration of the wood surface and putty surface when applying the finishing coat.

Cleaning of tools

Clean tools with water. Remove excess paint/ lacquer from tools and clean with water.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Wear protective gloves. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.