



Product Identifiers

Name: Vacmaster WD L20

SKU: VK1620SWC-01L

EAN: 6939349512896

Product Features:

Independently tested as Class L for the collection of light hazardous dusts, including soft woods, gypsum, plasterboard and Corian. Effective and reliable extraction that is suitable for lower-toxicity dusts with a workplace exposure limit (WEL) of greater than 1 mg/m³.

Powered by a 1600-watt twin fan bypass motor that delivers 260 Air Watts.

1390W power take-off socket. Plug in your power tool and connect up the suction hose to start extracting dust as you sand or drill.

Fitted with 2 stage HEPA filtration. Featuring a HEPA 13 cartridge filter and a HEPA 13 post-motor exhaust filter to protect against harmful dust particles recirculating into the ambient air. Capturing at least 99.95% of dust and allergen particles, down to 0.3 microns. A washable pre-filter is also included to pro-long the lifespan of the cartridge filter.

Stainless steel collection tank, friction fit extension tubes, reinforced steel retainer clips, air flow control handle and 3.5m crush resistant 35mm suction hose.

Technical Specifications

Voltage	240V
Motor Power	1600W
Tank Volume	20L
Actual Dry Capacity	12.7L
Actual Wet Capacity	10.1L
Power Take-off	1390W
Max Airflow	52L/s
Air Watts	260W
Tank Material	Stainless Steel
Noise Level	69 dB(A)
Max Vacuum Pressure	27KPa
Blower Function	No
Drainage Port	No
Suction Tubes	2pcs Stainless Steel
Airflow Control Handle	Yes
Hose Length	3.5m
Hose Diameter	35mm
Cord Length	5m
Working Reach	9.5m Approx.
Guarantee	1 Year Commercial Only Warranty

Product Dimension (mm)

Height	550 mm
Width	405 mm
Depth	400 mm

Packaging Dimensions (mm)

Height	480 mm
Width	525 mm
Length	390 mm