

Woodeedoo Decking Oil | Matt Finish

Safety & Usage Guide

Safe Handling

- Shake well before use – do not dilute.
 - Apply outdoors or in a well-ventilated area.
 - Wear protective gloves if applying for long periods.
 - Avoid contact with skin and eyes. If it happens, wash with water.
-

Important Safety Notice

Oil-soaked rags can self-ignite.

Always:

- Soak used rags in water immediately after use.
 - Store them in a closed metal container, or dispose of them safely.
 - Keep out of reach of children and pets.
 - Do not swallow.
-

Storage & Disposal

- Store in the original sealed container at +5 °C to +25 °C.
 - Keep away from heat, flames, or sparks.
 - Do not pour leftover oil into drains or watercourses.
 - Dispose of product and used cloths at local waste facilities in line with council guidelines.
-

Product Features

- Natural tung and linseed oil blend
- Transparent, matt finish
- Deep penetrating, breathable protection
- Protects decking, fences, pergolas & exterior wood
- Eco-friendly, low odour, easy to apply
- Non-flaking, enhances natural wood grain

 **Coverage & Drying**

- Coverage: 10–12 m² per litre (one coat)
- Recommended coats: 2–3
- Drying time: 24 hours per coat

 **Not Suitable For**

- Indoor use in unventilated spaces
- Direct contact with food or drinking water surfaces